





The Brighter Choice

Lamp-Free High-Brightness Projectors for Business & Education







The Brighter Choice for Business & Education

The Luminous Superior Series (LS Series) is a versatile lineup of lamp-free projectors built for business, education, and commercial spaces. With models ranging from mainstream to advanced, this series delivers stunning brightness and high-contrast visuals with up to 8,500 ANSI Lumens, ensuring clarity even in well-lit environments. Supporting screen sizes up to 300 inches, these projectors offer a cost-effective alternative to commercial displays. LAN control simplifies management, while flexible installation options ensure seamless integration into any setup. From boardrooms and classrooms to retail displays and event spaces, the LS Series delivers the power, reliability, and clarity professionals need—making it the ideal choice for AV solutions.



Lamp-Free Laser/LED light sources with up to 60,000 hours lifespan.



Easy Management LAN control and hassle-free software updates.



High Brightness Up to 8,500 ANSI Lumens for clear, vivid visuals.



Energy Saving Up to 51% less power use than competing projectors.



Seamless Collaboration Supports 21:9 ratio for MTR and wireless content sharing.



Flexible Installation Optical zoom, lens shift, and side projection capabilities.

Comprehensive Projection Solutions for Any Space



3,000 AL













8,500 AL







Exceptional Image Quality

Precision and Clarity for Every Professional Setting

ViewSonic LS Series high-resolution projectors bring professional presentations to life. From the crisp detail of WXGA and 1080p to the breathtaking clarity of 4K UHD, these projectors adapt seamlessly to a variety of business environments. Whether it's a bright conference room, a large auditorium, or a specialized application, they deliver unmatched precision and vivid imagery for any scenario.



Unmatched Brightness in Any Environment

Experience crystal-clear visuals in any setting with brightness levels ranging from 3,000 to 8,500 ANSI Lumens. Designed for meeting rooms, classrooms, commercial venues, and large auditoriums, these projectors ensure vibrant, sharp imagery with consistent brightness, even in well-lit or expansive environments.



Deep Contrast, Stunning Detail

Powered by advanced DLP technology, ViewSonic LS Series projectors deliver high contrast and exceptional depth. With 0.65" or 0.67" DMD chips from Texas Instruments, experience richer blacks, sharper details, and more immersive visuals.



Vibrant Colors for True-to-Life Golf Simulation



Enhance golf simulation with vibrant, true-to-life colors, powered by ViewSonic's advanced color-tuning technology. In Golf mode, greens and blues are more vivid, fairways pop with detail, and putting surfaces look strikingly realistic—creating a golf simulation experience that feels as close to the real thing as possible.

*Features vary by product

Seamless Collaboration & Efficient Device Management

Next-Gen Meeting Experience with 21:9 Aspect Ratio

The LS Series projectors support a 21:9 aspect ratio, making them ideal for Microsoft Teams Rooms front row mode. This widescreen format displays presentations, chat, notifications, and video feeds simultaneously, fostering a more immersive and collaborative meeting experience.





Hassle-Free Wireless Screen Sharing

Wirelessly display content from your devices to the projector using the ViewSonic ViewShare Wireless Screen Casting Kit. Powered by the projector's USB-A out port, it requires no network setup or software installation, ensuring a fast, secure, and seamless connection just plug in and start sharing instantly.

*ViewShare sold separately.



Centralized Control for Greater Efficiency



Compatible with Crestron, AMX, PJ Link, ATEN, and Extron AV management systems, the LS series projectors enable centralized control for streamlined device management and improved operational efficiency.

Effortless Installation with Versatile Setup Options

Flexible Placement with Lens Shift

Easily adjust the projection up, down, left, or right using the tool-free lens shift control knob. This allows for flexible installation without repositioning the projector, ensuring precise alignment even in restricted spaces.



Short Throw, Big Impact



The LS Series projectors deliver large images even in small spaces, with a short throw ratio as low as 0.44. Capable of projecting a 100 inches screen from just 0.95 meters away, they offer flexible installation, making an immersive viewing experience possible without requiring a large room.



Flexible Installation with Optical Zoom

With up to 1.7x optical zoom, achieving the ideal image size is effortless, eliminating the need to reposition the projector. Whether in conference rooms, classrooms, large auditoriums, or event spaces, optical zoom provides seamless adaptability to different room sizes and configurations.



*Features vary by product

Perfectly Shaped Images from Any Angle

Ensure precise image alignment with advanced keystone correction and 4-corner adjustment. Ideal for classrooms, exhibitions, and creative spaces, these features eliminate distortion and deliver a perfectly proportioned display—even from off-center angles.



Versatile Creative Applications



Capable of projecting at any vertical angle, the LS Series projectors can display images on ceilings, walls, or floors—ideal for museums, retail displays, and events. Portrait mode enhances versatility for projection mapping, staging, and creative advertising.



Hassle-Free Maintenance

Long-Lasting, Consistent Brightness

Designed with laser and LED light sources, the LS Series projectors deliver up to 60,000 hours of consistent brightness without requiring lamp replacement. Their extended lifespan reduces maintenance costs, time, and effort, ensuring reliable performance year after year.



Energy-Efficient and Cost-Effective



With up to 51% lower power consumption than competing technologies, the LS Series lamp-free projectors provide an energy-efficient, cost-saving solution that benefits both budgets and sustainability goals.

*Features vary by product

A Simpler Way to Update Projector Software

Avoid service center visits by updating your projector software easily via a USB cable connection to your laptop. This exclusive ViewSonic solution ensures hassle-free updates for optimal performance.

*The latest projector software updates can be found in the download section at the bottom of the product page when available.



DLP Technology for Reliable Performance



Engineered with DLP technology, the LS Series projectors maintain consistent color performance over time, free from yellowing. With a sealed engine design, they are filter-free, preventing dust buildup and reducing maintenance. Moreover, they deliver crisp, seamless visuals with remarkable contrast, eliminating the screendoor effect.

Specifications



	LS510W	LS560W			
	LS510WH	LS560WH	LSD300W-ST		
SRP	\$599	\$799	\$749		
Light Source Type	LED	LED	LED		
Native Resolution	WXGA	WXGA	WXGA		
Brightness (ANSI Lumens)	3,000	3,000	3,300		
Contrast Ratio	3,000,000:1	3,000,000:1	3,000,000:1		
Max. Light Source Life (hours)	30,000	30,000	30,000		
Projection Offset	100%±5%	110%±5%	110%±5%		
Throw Ratio	1.55-1.70	0.49	0.49		
Optical Zoom	1.1X	Fixed	Fixed		
Keystone Correction	V: ±40°	H: ±40°, V: ±40°	H: ±40°, V: ±40°		
Lens Shift	NA	NA	NA		
		Input			
Computer In	1	1/NA	1		
HDMI	1 (HDMI 1.4, HDCP 1.4)	1 (HDMI 1.4, HDCP 1.4)	1 (HDMI 1.4, HDCP 1.4)		
Audio In (3.5mm)	1	1	1		
		Output			
Monitor Out	1/NA	1/NA	1		
Audio Out (3.5mm)	1	1	1		
Speaker	2W	2W	2W		
USB-A (Power)	1 (5V/2A)	1 (5V/2A)	1 (5V/2A)		
	Control				
RS232 (DB 9-pin male)	1	1	1		
RJ45 (LAN control)	NA	1	1		
USB-A (Services)	1 (share with USB-A Output)	1 (share with USB-A Output)	1 (share with USB-A Output)		
		Others			
Power Consumption (Normal)	240W	229W	255W		
Net Weight	2.65kg	2.85kg	2.85kg		
Dimensions (WxDxH) with Adj. Foot	293x221x115mm	293x221x115mm	294x237x115mm		
		Feature Map			
Golf Mode		NA/			
LAN Control		٠	•		
MTR (21:9)					
Projector Software Update	•	•	٠		



	LS711W LS711HD	LS630W LS630HD	LS740W LS740HD	LS741HD
SRP	\$1,399 \$1,599	\$899 \$999	\$899 \$1,099	\$1,499
Light Source Type	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor
Native Resolution	WXGA / 1080p	WXGA / 1080p	WXGA / 1080p	1080p
Brightness (ANSI Lumens)	4,200	4,500/ 4,000	5,000	5,000
Contrast Ratio	3,000,000:1	3,000,000:1	3,000,000:1	3,000,000:1
Max. Light Source Life (hours)	30,000	30,000	30,000	30,000
Projection Offset	125%±10% / 132%±10%	124%±10% / 132%±10%	124%±10% / 132%±10%	132%±10%
Throw Ratio	0.52 / 0.5	1.18-1.54 / 1.13-1.47	1.18-1.54 / 1.13-1.47	1.4-2.24
Optical Zoom	Fixed	1.3X	1.3X	1.6X
Keystone Correction	H: ±15°, V: ±15°	H: ±30°, V: ±30°	H: ±30°, V: ±30°	H: ±30°, V: ±30°
Lens Shift	NA	NA	NA	NA
	Input			
Computer In	NA	NA	NA	NA
HDMI	2 (HDMI 1.4, HDCP 1.4)	2 (HDMI 1.4, HDCP 1.4)	2 (HDMI 1.4, HDCP 1.4)	2 (HDMI 1.4, HDCP 1.4)
Audio In (3.5mm)	NA	NA	NA	NA
	Output			
Monitor Out	NA	NA	NA	NA
Monitor Out Audio Out (3.5mm)	NA 1	NA 1	NA 1	NA 1
Audio Out (3.5mm)	1	1	1	1
Audio Out (3.5mm) Speaker	1 15W 1	1 15W 1	1 15W 1 (5V/1.5A)	1 15W 1
Audio Out (3.5mm) Speaker	1 15W 1	1 15W 1 (5V/1.5A)	1 15W 1 (5V/1.5A)	1 15W 1
Audio Out (3.5mm) Speaker USB-A (Power)	1 15W 1 (5V/1.5A)	1 15W 1 (5V/1.5A) Contr	1 15W 1 (5V/1.5A) ol	1 15W 1 (5V/1.5A)
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male)	1 15W 1 (5V/1.5A) 1	1 15W 1 (5V/1.5A) Contr 1	1 15W 1 (5V/1.5A) ol 1	1 15W 1 (5V/1.5A) 1
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control)	1 15W 1 (5V/1.5A) 1 NA 1 (share with	1 15W 1 (5V/1.5A) Contr 1 1 1 1 (share with	1 15W 1 (5V/1.5A) ol 1 NA 1 (share with USB-A Output)	1 15W 1 (5V/1.5A) 1 1 1 (share with
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control)	1 15W 1 (5V/1.5A) 1 NA 1 (share with	1 15W 1 (5V/1.5A) Contr 1 1 1 (share with USB-A Output)	1 15W 1 (5V/1.5A) ol 1 NA 1 (share with USB-A Output)	1 15W 1 (5V/1.5A) 1 1 1 (share with
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control) USB-A (Service) Power Consumption	1 15W 1 (5V/1.5A) 1 NA 1 (share with USB-A Output)	1 15W 1 (5V/1.5A) Contr 1 1 1 1 (share with USB-A Output) Othe	1 15W 1 (5V/1.5A) ol 1 NA 1 (share with USB-A Output)	1 15W 1 (5V/1.5A) 1 1 1 1 (share with USB-A Output)
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control) USB-A (Service)	1 15W 1 (5V/1.5A) 1 NA 1 (share with USB-A Output) 210W	1 15W 1 (5V/1.5A) Contr 1 1 1 1 1 1 1SB-A Output) Other 175W	1 15W 1 (5V/1.5A) ol 1 NA 1 (share with USB-A Output) rs 210W	1 15W 1 (5V/1.5A) 1 1 1 1 (share with USB-A Output) 210W
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control) USB-A (Service) Power Consumption (Normal) Net Weight Dimensions (WxDxH)	1 15W 1 (5V/1.5A) 1 NA 1 (share with USB-A Output) 210W 3.15kg	1 15W 1 (5V/1.5A) Contr 1	1 15W 1 (5V/1.5A) ol 1 NA 1 (share with USB-A Output) rs 210W 3.00kg 286x216x129mm	1 15W 1 (5V/1.5A) 1 1 1 1 (share with USB-A Output) 210W 3.00kg
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control) USB-A (Service) Power Consumption (Normal) Net Weight Dimensions (WxDxH)	1 15W 1 (5V/1.5A) 1 NA 1 (share with USB-A Output) 210W 3.15kg	1 15W 1 (5V/1.5A) Contr 1	1 15W 1 (5V/1.5A) ol 1 NA 1 (share with USB-A Output) rs 210W 3.00kg 286x216x129mm	1 15W 1 (5V/1.5A) 1 1 1 1 (share with USB-A Output) 210W 3.00kg
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control) USB-A (Service) Power Consumption (Normal) Net Weight Dimensions (WXDXH) with Adj. Foot	1 15W 1 (5V/1.5A) 1 NA 1 (share with USB-A Output) 210W 3.15kg 286x216x129mm	1 15W 1 (5V/1.5A) Contr 1	1 15W 1 (5V/1.5A) ol 1 NA 1 NA 1 (share with USB-A Output) rs 210W 3.00kg 286x216x129mm	1 15W 1 (5V/1.5A) 1 1 1 1 (share with USB-A Output) 210W 3.00kg
Audio Out (3.5mm) Speaker USB-A (Power) RS232 (DB 9-pin male) RJ45 (LAN control) USB-A (Service) Power Consumption (Normal) Net Weight Dimensions (WXDXH) with Adj. Foot	1 15W 1 (5V/1.5A) 1 NA 1 (share with USB-A Output) 210W 3.15kg 286x216x129mm	1 15W 1 (5V/1.5A) Contr 1	1 15W 1 (5V/1.5A) ol 1 NA 1 NA 1 (share with USB-A Output) rs 210W 3.00kg 286x216x129mm	1 15W 1 (5V/1.5A) 1 1 1 1 (share with USB-A Output) 210W 3.00kg

Specifications



	-0				
	LS901HD LS901-4K	LS950WU LS950-4K	LS951WU	LS960WU	
SRP	\$2,299 \$2,999	\$4,299 \$5,499	\$5,799	\$4,999	
Light Source Type	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	
Native Resolution	1080p / 4K	WUXGA / 4K	WUXGA	WUXGA	
Brightness (ANSI Lumens)	6,000 / 5,500	7,100	8,000	8,500	
Contrast Ratio	3,000,000:1	3,000,000:1	3,000,000:1	3,000,000:1	
Max. Light Source Life (hours)	30,000	30,000	30,000	30,000	
Projection Offset	154% ±10%	0%±10%	0%±10%	0%±10%	
Throw Ratio	1.2-2.04	1.25-2.00	0.75-0.95	1.25-2.00	
Optical Zoom	1.7X	1.6X	1.26X	1.6X	
Keystone Correction	H: ±30°, V: ±30°	H: ±30°, V: ±30°	H: ±30°, V: ±15°	H: ±30°, V: ±30°	
Lens Shift	H: NA V: 0%, -21%	H: +25%, -25% V: +55%, -55%	H: +25%, -25% V: +55%, -55%	H: +25%, -25% V: +55%, -55%	
		Input			
Computer In	NA	1/NA	1	1	
HDMI	2 HD: (HDMI 2.0, HDCP 2.2 HDMI 1.4, HDCP 1.4) 4K: (HDMI 2.0, HDCP 2.3)	2 (HDMI 2.0, HDCP 1.4/2.2)	2 (HDMI 2.0, HDCP 1.4/2.2)	2 (HDMI 2.0, HDCP 1.4/2.2)	
Audio In (3.5mm)	NA	1/NA	1	1	
		Output	:		
Monitor Out	NA	NA	NA	NA	
Audio Out (3.5mm)	1	1	1	1	
Speaker	15W x2	10W x2	10W x2	10W x2	
USB-A (Power)	1 (5V/1.5A)	1 (5V/1.5A)	1 (5V/1.5A)	1 (5V/1.5A)	
	Control				
RS232 (DB 9-pin male)	1	1	1	1	
RJ45 (LAN control)	1	1	1	1	
USB-A (Services)	1 (share with USB-A Output)	NA	NA	NA	
		Others			
Power Consumption (Normal)	245W	405W/450W	560W	545W	
Net Weight	4.77kg / 4.85kg	12.8kg / 14.1kg	13.0kg	13.7kg	
Dimensions (WxDxH) with Adj. Foot	337x280x132mm	486x433x186mm	486x395x186mm	486x433x186mm	
		Feature M	lap		
Golf Mode	٠	(Sports Mode)	(Sports Mode)	(Sports Mode)	
LAN Control	•	•	•	•	
MTR (21:9)		•	•	•	
Projector Software Update	•	•	•	•	



	LSC520WU LSC521WU	LSC600WU-ST LSC601WU-ST	LSC700-4K LSC701-4K	LSC800WU LSC801WU	
SRP	\$1,999 \$2,099	\$2,899 \$2,999	\$4,899 \$4,999	\$4,899 \$4,999	
Light Source Type	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	
Native Resolution	WUXGA	WUXGA	WUXGA with 4K Enhancement	WUXGA	
Brightness (ANSI Lumens)	5,200	6,000	7,000	8,000	
Contrast Ratio	3,000,000:1	3,000,000:1	3,000,000:1	3,000,000:1	
Max. Light Source Life (hours)	30,000	30,000	30,000	30,000	
Projection Offset	0%±5%	98%±5%	0%±5%	0%±5%	
Throw Ratio	1.08-1.76 / 1.2-2.0	0.44	1.2-2.0	1.2-2.0	
Optical Zoom	1.6X	Fixed	1.6X	1.6X	
Keystone Correction	H:±30° , V:±30°	H: ±15° , V: ±15°	H: ±25° , V:±30°	H: ±25° , V:±30°	
Lens Shift	520: H: NA; V: +45%, 0% 521: H: NA; V: +60%, 0%	NA	H: +29%, -29% V: +66%, 0%	H: +29%, -29% V: +60%, 0%	
	Input				
Computer In	1	1	NA	1	
HDMI	2 (HDMI 1.4, HDCP 1.4)	2 (HDMI 1.4, HDCP 1.4)	2 (HDMI 2.0, HDCP 1.4/2.2)	2 (HDMI 1.4, HDCP 1.4)	
Audio In (3.5mm)	1	NA	1	1	
HDBaseT	NA / 1	NA / 1	NA / 1	NA / 1	
USB-A	1 (5V/1.5A)	1 (5V/2A)	2 (5V/2A)	1 (5V/2A)	
		Outpu	t		
Monitor Out	1	1	NA	1	
Audio Out (3.5mm)	1	1	1	1	
Audio Out (HDMI ARC)	NA	NA	1 (Share with HDMI Input)	NA	
Speaker	16W	16W	16W	16W	
USB-A (Power)	1 (USB2.0 - 5V/1.5A, share with USB-A Input)	1 (USB2.0 - 5V/2A, share with USB-A Input)	1 (USB2.0 - 5V/2A, share with USB-A Input)	1 (USB2.0 - 5V/2A, share with USB-A Input)	
		Control			
RS232 (DB 9-pin male)	1	1	1	1	
RJ45 (LAN control)	1	1	1 (share with RJ45 Internet)	1	
USB-A (Services)	NA	NA	1 (share with USB-A Output)	NA	
		Others			
Power Consumption (Normal)	230W / 240W	335W / 345W	380W / 390W	375W / 385W	
Net Weight	5.2kg	8.0kg	7.9kg	7.9kg	
Dimensions (WxDxH) with Adj. Foot	390x294x128mm	405x404x164mm	405x358x137mm	405x358x137mm	
		Feature M	1ар		
Golf Mode	•	•	•	•	
LAN Control	•	•	•	•	
MTR (21:9)	•	•	•	•	
Projector Software Update					



ViewSonic 🕍

www.viewsonic.com

Copyright All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All specifications are subject to change without written notice. Images are for illustrative purpose only. Offers and programs may vary by country. Please contact your local ViewSonic office for more information. Copyright © ViewSonic Corporation 2000-2025. All rights reserved.

Contact a **ViewSonic Expert** to Book a Demo

